

PAINT REMOVER

Special solvent for epoxy and polyurethane paints

- ▷ **For removal of paints, varnishes, coatings**
 - ▷ **Non-flammable**
 - ▷ **Low Toxicity**
 - ▷ **Non-VOC**
-

Description

PAINT REMOVER is a general-purpose liquid solvent used to remove stains such as epoxy or grout, waxes, inks, acrylic varnishes as well as for degreasing metals. It is applied to smooth or mineral coatings, facilitating cleaning without damaging them.

Typical Applications

PAINT REMOVER can be applied to facilitate stain removal in the following cases:

- Remove any paints, graffiti, etc.
 - Acrylic varnishes
 - Residues of gasoline
 - Epoxy and polyurethane paints
 - Adhesive residues and epoxy joints created during the bonding of ceramic tiles
-

Technical Data

Product identification

Consistency	Liquid
Color	Transparent
Chemical substance	Mix of esters
Density	1,09 ± 0,05 kg/L

Application procedure

Application

Before applying PAINT REMOVER, protect any surface that may be damaged when in contact with solvents. Apply PAINT REMOVER as it is without dilution, evenly, with a brush. When the coating has softened (5 - 10 minutes) with a soft brush or cloth lightly rubbing the surface, remove residues. In difficult places, repeat the procedure if necessary. Finally rinse the surface with cold water and detergent.

Recommendations

- Do not use PAINT REMOVER on synthetic surfaces such as rubber, polystyrene, vinyl flooring etc.
- Not compatible with synthetic fabrics and fiberglass
- Do not use in good quality wood without testing
- Do not apply at the substrate and ambient temperatures lower than + 5 °C and higher than + 35 °C

Consumption

Depending on the application 50 – 80 ml/m².

Storage

PAINT REMOVER remains stable for at least 24 months from the production date in the original sealed packaging stored in a dry place and temperature between +5°C and +35°C.

Packaging

Buckets of 1L.

Safety Instructions

For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety-related data.

Legal Notes

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice.

Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one

responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr